



**BACKUP/RECOVERY SYSTEM AND
METHODS FOR PROTECTING A COMPUTER SYSTEM**

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a backup/recovery technique for a computer system, and more particularly to a method for protecting a computer system with a backup/recovery system.

2. Description of Prior Art

The protection for the computer system is an important issue for a computer user at present. Chain mails for the spread of virus by way of Internet are increasingly overabundance in virtue of vigorous development of network. Modern people get used to E-mails (electronic mails) as the connecting interface between human beings. Afterwards, they often receive greetings and messages sent out from others, as well as the annoying ~~spams~~ spam. ~~And~~ Further, it is impossible to guard against viruses smuggled by concealing in between the mails.

Computer viruses are buried or hidden in another program. Once the program is executed, the virus is activated and attaches itself to other programs in the system. Nowadays, viruses are frequently spread by the smuggling with files in a predetermined

form, such as *.EXE, *.DOC, and *.ZIP form attached to the e-mails. When the user is ignorant of what happened and operates the attached files, the computer will be affected by poison. Viruses will send themselves to the entire ~~name~~mailing list of the users' record of communication. If the users relax their vigilance and operate the virus-smuggled files, there will be a chain-infected reaction that causes the disaster worldwide.

Moreover, for the PC (personal computer) users, they will risk interconnecting of computers into networks. In ~~case of~~ the viruses infect~~ed~~ their users' computers, viruses usually destroy the files throughout the ~~user's disks~~ and all computer files may be deleted that lose the essential data in the twinkling of an eye and cause the computer system operation out of order. If files in the operating system files have been infected and destroyed, the operating system, such as Windows, cannot be rebooted. The more serious effect ~~such~~ is that the computer system needs to be ~~re~~-setup again. Hence, there is a need for eliminating viruses from computers and networks.

Conventionally, a used backup/recovery software, although having the backup/recovery function, it is capable of executing the backup program for backing up data, also of executing the recovery program for restoring the data to the hard disk (HD), in order to protect the HD with the function of returning to the a normal state. Nevertheless, not only the HD is not thoroughly protected ~~thoroughly~~, but also the backup/recovery ~~aeoperation~~ always wastes the user a ~~long~~ lots of time.

For instance, the conventional ~~a prior~~ Ghost backup/recovery software, such as the Ghost software developed ~~researched by~~ Symantec Corporation ~~in U.S.A.~~, its backup/recovery action needs the network administrator to operate the operating system (OS)

before he/she manually operates the Ghost a backup/recovery
program manually. The Ghost software includes a backup program
to backs up all data stored in the selected hard
disk/partition/hard disk to a file totally. In addition, it
further includes and Ghost-recovery program to restores the data
from the file to the selected hard disk/partition/hard disk.
Prior to backing up the data, the Ghost software stops all other
tasks in the computer. All running applications are closed before
the backup procedure. It then is a single task procedure to
creates a the backup file, with Ghost that the backed-up data,
in a single task procedure. all of other tasks should stop ahead,
This backup procedure takes
and it spends a period of time about 8 minutes per Gigabyte/ Gb,
in general. Since Besides, owing to the Ghost software backs up
all the valid data stored in the hard disk, the space of the hard
disk for backing up data itself backed up occupied by the Ghost
software occupies an is extremely large space in the hard disk.
The All data provided currently that being used in by the file
system of the operating system (OS) will be backed up the belonged
area into the backup file absolutely, nevertheless whether such
related data it has been changed or not afterwards in the past,
thereby occupying causing a great amount of space in the hard
disk being occupied.

Further, some presently available another prior

backup/recovery software, such as the Goback software developed, designed by Aadaptec Corporation in U.S.A., it operates the its recovery ~~action~~ program without the need of operating the operating system (OS) in advance. While ~~The system is indicated to initiatinge the a~~ recovery operation, and then the Goback software recovers the hard disk to a selected status. When the computer system is destroyed, the ~~aeoperation~~ of restoring the hard disk files also needs the network administrator to implement ~~operate~~ the recovery program manually.

Obviously, when the computer system is surfing the web or receiving electronic mails accesses by ~~multiple the~~ users, the virus ~~wouldill~~ be easily infected the user's hard disks. The virus will ~~further then~~ break out that causes the accidental damage of the computer system. ~~damaged unexpectedly~~ Moreover, if the virus is successful, more serious effects such as the computersystem cannot be booted from either the hard disk or the floppy. Nevertheless, the conventional ~~used~~ backup/recovery software is unable to effectively distinguish the possible danger of receiving data from the Internet ~~effectively~~, not to mention the fact that it is incapable of backing up data promptly ~~immediately~~.

Conversely, various conventional ~~prior art~~ devices have been proposed for the detection of virus intrusions on the computer system. For example, the ~~The~~ InterScan VirusWall developed

~~produced~~ by Trend Micro Corporation, it provides Internet gateway protection against viruses and malicious code. The detection is for all SMTP, HTTP, and FTP Internet traffic at the gateway and blocks malicious mobile code at the gateway. It can be configured to respond to virus detection and security violation incidents in three ways, such as alerts the system administrator, just deletes the infected file or permits the user to download the file under

certain controlled conditions, optionally isolates the infected file for later treatment.

The previous anti-virus software may provide Internet real-time virus detection during surfing the web and blockage of viruses included with electronic mails, however, the backup/recovery technique is not available in such anti-virus software. This results in a harm of the hard disk for a computer system, in a situation of the undefined viruses. As described above, the anti-virus software cannot backs up and or-recover data in the hard disk ~~retrieves data~~. Hence, in case of contingency, the computer system is destroyed ~~damaged~~, the disks cannot return to the normal state ~~immediately~~. The demand of real-time backup/recovery for the user cannot be ~~satisfied~~ served well.

Accordingly, because of the presently anti-virus software doesn't contains ~~without~~ backup/recovery function and current ~~other~~ backup/recovery software products cannot recognize the

possible danger of receiving data from the Internet to protect the computer system ~~as well~~, There is a need in the art to provide a backup/recovery software for protecting a computer system much more efficiently.

The present invention overcomes the limitations and shortcomings of the prior art with systems and methods for protecting a computer system with files automatically backed up to the data storage device, such as a hard disk ~~automaticallly~~ prior to downloading data to the end-users' computers. It will be appreciated that the system and method of the present invention may provide computer system protection from viruses introduced by data downloaded from the largely unregulated network.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to provide a backup/recovery system and methods, which can be used in a computer system to securely backs up and reliably retrieves data. The improvement is remarkable for the data storage ~~means~~ device while its data is under whole automatic protection from viruses.

To achieve the above and other objects, this invention applies a detecting module in the backup/recovery system to monitor a predetermined datamessage to be downloaded to the computer system. When a predetermined datamessage is arrived to

the computer system received, the detecting module determines whether there is a predetermined harmful data contained in the predetermined datamessage. If there is a predetermined harmful data contained therein, the backup/recovery system backs up data automatically prior to downloading the predetermined ~~such~~ data, so as to protect the computer system.

One aspect of the present invention involves a backup/recovery system for detecting and backing up data immediately. The backup/recovery system is installed in a computer system. The computer system includes an application layer, which coupled to an interface. The backup/recovery system comprises a detecting module, located within the computer system, for monitoring a predetermined ~~message~~ data. The detecting module retrieves the predetermined datamessage, in order to determine whether there is a predetermined harmful data contained therein for judging the backup/recovery system to backup data or not. The interface implements a predetermined procedure thereafter and the application layer involves ~~reading~~ accessing the predetermined datamessage.

Another aspect of the present invention involves a method for protecting a computer system. The method comprises three steps. First, the backup/recovery system retrieves a predetermined datamessage to be downloaded to the computer system. Secondly, upon retrieval of a predetermined datamessage

to be downloaded, determines whether a predetermined harmful data is contained in the predetermined datamessage. If there is predetermined harmful data ~~is contained~~ therein, the data stored in the computer system is backed up eventually, in order to enable the computer system to return the data storage devicemeans to a ~~preceeding~~previous state ~~us while at the time~~ the viruses infect the data storage devicemeans.

Further aspect of the present invention involves a method for protecting a computer system with a backup/recovery system. The computer system includes an application layer coupled to an interface. The method comprises several steps. First, the backup/recovery system installs in the computer system. The backup/recovery system comprises a detecting module for monitoring a predetermined ~~message~~data located within the computer system. Secondly, the detecting module retrieves the predetermined datamessage to be downloaded to the computer system. Upon retrieval of a predetermined datamessage to be downloaded, determines whether a predetermined harmful data is contained in the predetermined datamessage. If the ~~is~~ predetermined harmful data is contained, the data stored in the computer system is backed up. Then, the interface implements a predetermined procedure. Eventually, the application layer is indicated to ~~read~~access the predetermined message.

In the preferred embodiment of the invention, the

backup/recovery system is coupled to a network device. The network device ~~is~~ can be coupled to at least one client device by a communications link. The network device can be ~~is~~ coupled to a server device. The server device is capable of controlling the client device's backup/recovery ~~conduct~~ operation remotely and immediately. The network device comprises a network means, comprising one or more of the group consisting of a LAN, WAN, Internet, Intranet, Extranet and wireless network. The network device comprises a communication means, comprising one or more of the group consisting of electronic mail, TCP/IP sockets, RPC, HTTP, and IIOP. The predetermined harmful data comprises a file which is of a type that can contain viruses ~~in a predetermined form, comprising one or more of the group consisting of~~ such as *.EXE, *.DOC, and *.ZIP extension file ~~form~~.

It is to be understood that both the foregoing general description and the following detailed description are exemplary, and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The above-mentioned objects and other objects and features of this invention and manner of attaining them will become apparent, and the invention itself will be understood by reference to the following description of the preferred

embodiments of the invention taken in conjunction with the accompanying drawings, wherein:

FIG. 1 illustrates parts of a computer system with a backup/recovery system as ~~per~~-an embodiment of the invention;

FIG. 2 illustrates a flowchart of the computer system with a backup/recovery system as ~~per~~-an embodiment of the invention; and

FIG. 3 illustrates a schematic diagram of the hard disk return to a ~~state of the preceding~~previous state for protecting the computer system as ~~per~~-an embodiment of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Reference will now be made in detail to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

The present invention contemplates a backup/recovery system to provide protection for the computer system by way of a detecting module of the backup/recovery system. The real--time backup/recovery system adopts a technique for detecting network data to be downloaded to the computer system, such as data

retrieved from an Internet content server in response to a browser request, which can automatically backup any file alteration to the hard disk. Here is referred to the data to be downloaded, it being understood that the invention is capable of use in various other combinations and environments and is capable of changes or modifications within the scope of the inventive concepts as expressed hereunder.

The preferred embodiment of the present invention provides a backup/recovery system installed in the computer system. The computer system comprises at least an application layer, which coupled to an interface. The application layer is used for operating a predetermined application program. The backup/recovery system comprises a detecting module, located within the computer system, for monitoring a predetermined ~~message~~data.

When the predetermined data~~message~~ is received, the detecting module determines whether there is a predetermined harmful data contained in the predetermined data~~message~~. If there is a predetermined harmful data contained therein, the backup/recovery system backs up data stored in the hard disk, and the interface implements a predetermined procedure thereafter, so that application layer can ~~read~~access the predetermined ~~message~~data.

With reference to FIG. 1, according to an embodiment of the

present invention a backup/recovery system may recognize the possible danger of receiving data from network effectively, and may create a restorer~~restoration~~ point immediately to backup data as well.

The computer system includes an application layer 2 and a driver layer 4. The application layer 2 is used for operating a predetermined application program, and the driver layer 4 is used for operating a predetermined driver program. The application layer 2 is coupled to an interface, which installs the corresponding protocol module stored therein at the time of initiating.

The application layer 2 is a layer for operating the application program. The application layer 2 has an Internet Application interface 20. All of the network application programs, such as Internet Explorer, Outlook Express, FTP utilities and TELNET utilities, are operated at the application layer 2.

The driver layer 4 is a layer for operating the driver program. All of the network driver programs are operated at the driver layer 4. The driver layer 4 provides the network access service for the application program, and accesses LAN (local area network) and distributed system (Internet) 6 through the network interface card or other network system. The driver layer 4 has a network driver interface 40.

The backup/recovery system may couple to a network device. The network device is coupled to at least one client device by a communications link. The network device is coupled to a server device. The server device is capable of controlling the client device's backup/recovery ~~conduct~~ operation remotely and immediately. The network device comprises a network means, comprising one or more of the group consisting of a LAN, WAN, Internet, Intranet, Extranet and wireless network. The network device comprises a communication means, comprising one or more of the group consisting of electronic mail, TCP/IP sockets, RPC, HTTP, and IIOP.

The backup/recovery system comprises a detecting module 42, a network monitor driver. The detecting module 42 may get into the application layer 2 or the driver layer 4 upon the backup/recovery system is installed in the computer system. While in the preferred embodiment of the present invention, the detecting module 42 of the backup/recovery system gets into the driver layer 4 for monitoring a predetermined ~~message~~ data to be downloaded to the computer system.

When the predetermined data ~~message~~ is received, the detecting module 42 retrieves the data ~~message~~. The predetermined data ~~message~~ is coming from the behavior of downloading from the network or ~~the~~ receiving electronic mails via Outlook Express, comprising HTTP pages, E-mails, downloading files and so forth.

Furthermore, the detecting module 42 determines whether there is a predetermined harmful data contained in the predetermined ~~message~~data, in order to judge whether the backup/recovery system creates a ~~restore~~restoration point to backup data stored in the hard disk. The predetermined harmful data includes the possible harmful data, which comprises a file in a predetermined form, comprising one or more of the group consisting of *.EXE, *.DOC, and *.ZIP extension file~~form~~. Other types of files are included as well.

That is, the detecting module 42 will retrieve all downloading data the application layer 2 call on the network and or the receiving electronic mails via Outlook Express. The detecting module 42 monitors the data to be downloaded to the computer system. If there is a predetermined harmful data contained therein, the backup/recovery system may create a ~~restore~~restoration point immediately to backup data as well prior to downloading data to the end-users' computers.

Thereafter, the detecting module 42 ~~sends~~transfers the predetermined ~~message~~data to the computer system. After the interface implements a predetermined procedure, such as dealing with the protocol module and the uniform format handling for the ~~re~~eearrived data, the application layer 2 is informed to ~~read~~ access the predetermined data~~message~~.

Thereupon, if the ~~re~~eearrived data cause damage to the

computer system, it is capable of returning the storage device to the ~~preceeding~~previous condition state immediately.

Accordingly, the backup/recovery system as ~~per~~ the preferred embodiment of the present invention installed in the computer system may monitor all information from the network. Once it detects the downloading ~~conduct~~operation or the electronic mails received by Outlook Express, it creates a ~~restore~~restoration point immediately with the valid data.

The detecting module 42 monitors all information from the network entirely. Therefore, if viruses and malicious code smuggling with the downloading data or the receiving electronic mails that activated and caused the system crash, the system still can return to the normal state.

The present invention meditates a method for protecting a computer system. The method comprises three steps. First, the backup/recovery system retrieves a predetermined ~~message~~data to be downloaded to the computer system. Secondly, upon retrieval of a predetermined ~~message~~data to be downloaded, determines whether a predetermined harmful data is contained in the predetermined ~~data~~message. If the ~~is~~ predetermined harmful data is contained, the data stored in the computer system is backed up eventually, in order to enable the computer system to return the data storage ~~devicemeans~~ to a ~~preceeding~~previous state ~~while at the time~~ the viruses infect the storage ~~devicemeans~~.

In the preferred embodiment of the invention, the present invention contemplates a method for protecting a computer system with a backup/recovery system. The computer system includes an application layer coupled to an interface. First, the backup/recovery system installs in the computer system. The backup/recovery system comprises a detecting module for monitoring a predetermined datamessage ~~arrived to~~ ~~located within~~ the computer system. Secondly, the detecting module retrieves the predetermined datamessage to be downloaded to the computer system. Upon retrieval of a predetermined datamessage to be downloaded, determines whether a predetermined harmful data is contained in the predetermined datamessage. If the ~~is~~ predetermined harmful data is contained, the data stored in the computer system is backed up. Then, the interface implements a predetermined procedure. Eventually, the application layer is indicated to ~~read-access~~ the predetermined datamessage.

FIG. 2 illustrates a flowchart of the computer system with a backup/recovery system as ~~per~~ an embodiment of the invention. First of all, Step S10 is to monitor the ~~message-data~~ datamessage to be downloaded to the computer system. Upon the datamessage is arrived; the detecting module 42 retrieves the datamessage and determines the datamessage in advance.

Step S30, a second step, is to ascertain by the detecting module 42, whether the network datamessage is downloaded to the

computer system. The detecting module 42 analyzes the contents contained in the messagedata and determines whether the messagedata is the predetermined messagedata the users applied required to be downloaded. If not, then goes to Step S90, and ~~sends~~ transfers the messagedata to the upper layer.

If yes, then goes to Step S50. The predetermined messagedata is coming from the behavior of downloading from the network or ~~the-receiving~~ electronic mails via Outlook Express, comprising HTTP pages, E-mails, downloading files and so forth.

Step S50, a third step, is to determine further whether the messagedata contains a predetermined harmful data by the detecting module 42. For example, the possible harmful data may comprise a file in a predetermined form, comprising one or more of the group consisting of *.EXE, *.DOC, and *.ZIP form. If not, such data like TXT, bitmap, then goes to Step S90 either, and the detecting module 42 ~~sends~~ transfers the messagedata to the upper layer.

If yes, then goes to Step S70. The backup/recovery system creates a restorerestoration point automatically to backup data prior to downloading data to the computer system.

Step S90, a final step, is to send data by the detecting module 42. After the interface implements a predetermined procedure, such as dealing-processing with the protocol module and the uniform format handling for the received data, the

application layer 2 is informed to ~~read~~ access the predetermined messagedata.

Hence, if the ~~reccc~~arrived data cause damage to the computer system, it is capable of returning the storage device to the ~~preceeding~~previous ~~condition~~ state immediately.

The flow of creating a restorer~~restoration~~ point in Step S70 is to scan the entire disk recognizing the valid data. Each restorer~~restoration~~ point contains the messagedata of which data in the disk is valid data. While creating a restorer~~new restoration~~ point, the information of the valid data is stored therein.

Please be noted that the MSTCP protocol, which is defined by the Microsoft, is communicated with the Http/Ftp/Pop3 application protocols through TDI (Transport Driver Interface) layer. In the preferred embodiment of the present invention, the detecting module 42 is intercepting network data at a TDI layer.

The Http/Ftp/Pop3 application protocol ~~sends~~ transfers data to Internet through TdiSendEntry(), the entry function of TDI layer, and while Internet sends data back, MSTCP protocol produces an event. An event handler function set by SetEventEntry() handles this event, TDI_EVENT_RECEIV. If we change the address of the function entry, the function entry of TdiSendEntry() and SetEventEntry(), then we can intercept the network data.

When we operate Outlook Express to receive mails, Outlook

Express will send a request of receiving mails to the mail server on the Internet. All data Outlook Express sent to Internet will pass through the TDI layer, and the driver program of the backup/recovery system located in the TDI layer will recognize that the user is going to receive mails, and the driver program revise the ~~address~~ entry address of the event returning mails from the mail server on the Internet.

While the received~~ing~~ mails send back from the mail server, system will use event handler function of the driver program. The event handler function handles the data contained in the mails. If there are viruses or ~~unsafe~~ dangerous files ~~founded~~ detected in the mails, the driver program ~~of~~ at the TDI layer will inform the driver program of the backup/recovery system as ~~per~~ the preferred embodiment of the present invention of creating a ~~new restore~~ restoration point.

In the preferred embodiment of the present invention, the ~~new-restore~~ restoration point ~~is stored~~ the information of the valid data. In the process of backing up data, the data ~~demanded~~ needs to be backed up is stored in the ~~new-restore~~ restoration point.

After that, the driver program sends the mails to Outlook Express. Therefore, ~~if~~ the users read their mails that caused the disk being damaged, then the user ~~may~~ might return the disk to a ~~state of the preceeding~~ previous state.

With reference to FIG. 3, according to an embodiment of the present invention a backup/recovery system may return the data storage device disk to a ~~state of the preceding~~previous state. The state A of the hard disk in the computer system is in normal conditions. However, the detecting module 42 determines the predetermined ~~messagedata~~data is contained a predetermined harmful data, and the backup/recovery system creates a restore~~new~~ ~~restoration~~ point to backup data.

Right after that, the detecting module 42 ~~sends~~transfers the predetermined ~~messagedata~~data to the computer system. The network interface implements a predetermined procedure thereafter and the application layer 2 involves ~~reading~~accessing the predetermined ~~messagedata~~data. The user probably downloads a virus-infected program, UNKNOWN.EXE, but the user has no idea.

The predetermined ~~messagedata~~data is with viruses, and the state B of the hard disk in the computer system is in abnormal conditions. Then, viruses are activated and ~~damage~~the computer system is damaged, as shown in FIG. 3, the state C of the hard disk in the computer system is in destroying conditions.

Nevertheless, ~~if~~while there is an accident, the user can return the disk to a ~~state of the preceding~~previous state with the backup/recovery system as ~~per~~the preferred embodiment of the present invention. The computer system is easily infected viruses while the user downloads data or ~~reads~~receives mails, but the

hard disk is capable of returning the hard disk to a normal state due to the backup/recovery system in the preferred embodiment of the present invention backs up the valid data being changed ~~stored~~ in the hard disk prior to downloading data to the computer system. Consequently, the system and the programs will never be lost or destroyed.

While this invention has been particularly shown and described with reference to embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

ABSTRACT OF THE DISCLOSURE

A1
A backup/recovery system and methodology that securely backs up and reliably retrieves data in a computer system. According to the invention, the backup/recovery system is utilized for protecting thea computer system, having a data storage devicemeans, such as a hard disk, with data stored thereon, on which ~~data-real-~~ time data backup protection is ~~des~~required, in order to receive data from ~~network system~~LAN/WAN afterwards without risk. In one embodiment of the invention, the backup/recovery system is installed in the computer system. The computer system includes an application layer coupled to an interface and operated predetermined application programs. A detecting module is located within the computer system for monitoring a predetermined ~~message~~ data to be downloaded to the computer system. When the predetermined ~~data~~message is ~~arreeived~~ to the computer system, the detecting module determines whether there is a predetermined harmful data contained in the predetermined ~~data~~message. If there is a predetermined harmful data contained therein, the backup/recovery system backs up data, and the interface implements a predetermined procedure thereafter, so that application layer can ~~access~~read the predetermined ~~data~~message safely.